

# SAFETY DATA SHEET

ISCEON 49

Page: 1 / 8

Date: 07/09/2004

Version: 3.03 UK

Cancel and replaces version: 2.00 UK

## 1 Product and company identification.

PRODUCT NAME : ISCEON 49  
Use : Refrigerant.  
SUPPLIER : Manufacturer :  
Name : Rhodia Organique Fine Limited.  
Address : PO Box 46 - St Andrews Road - Avonmouth - BRISTOL - BS11 9YF - England  
Telephone number : (44) 0117 948 4242  
Telefax number : (44) 0117 948 4249.  
Telephone number : (44) 0117 938 1289  
**EMERGENCY TELEPHONE NUMBER** : **00 44 117 938 1289 (UK: 0117 938 1289)**

## 2 Composition / information on ingredients

### >> PREPARATION

Chemical nature : Predominantly hydrofluoroalkane mixture. [\*]  
1,1,1,2-TETRAFLUOROETHANE : 88 %  
EC N° :212-377-0 (CAS : 811-97-2)  
OCTAFLUOROPROPANE : 9 %  
EC N° :200-941-9 (CAS : 76-19-7)  
Components presenting hazards : IsoButane (CAS: 75-28-5) : 3 %  
- EC Classification : (200-857-2) : F+ - R 12 [\*]  
>>Further information : R-413A

## 3 Hazards identification

### MOST IMPORTANT HAZARDS

#### Adverse human health effects

: Contains a liquefied gas. Contact of liquid may cause frostbite and injury to the cornea.

#### Main symptoms

: May have a narcotic effect at high concentrations.

#### Physical and chemical hazards

##### - Fire or explosion

: Heating will cause a rise in pressure with a risk of bursting. On combustion, toxic gases are released.

#### Specific hazards

: According to EC criteria, this product is not classified as a "hazardous preparation".

---

## SAFETY DATA SHEET

---

ISCEON 49

Page: 2/8

Date: 07/09/2004

Version: 3.03 UK

Cancels and replaces version: 2.00 UK

---

### 4 First-aid measures

- Inhalation : Move the person away from the contaminated area.  
Make the affected person rest.  
Always obtain medical attention.  
Show this sheet to the doctor. [\*]
- Skin contact : Contact of liquid with the skin:  
Rinse immediately with plenty of warm water.  
Immediately remove contaminated clothing or footwear.  
If it sticks, do not pull it off.  
Cover the affected area with a sterile dressing.  
Transfer to hospital immediately.
- Eye contact : Contact of liquid with the eyes:  
Rinse with water whilst keeping the eyes wide open.  
Always obtain medical advice, even if there are no symptoms.  
Show this sheet to the doctor. [\*]
- Ingestion : Not specifically applicable.
- Notes to the physician : Avoid administering adrenaline or any other similar products.
- Further information : Place contaminated clothing in a sealed bag for disposal. Use appropriate protective equipment when treating a contaminated person. [\*]
- 

### 5 Fire - fighting measures

- Extinguishing media
- Suitable : All extinguishing agents can be used.
  - Not suitable : None. If there is a fire close by, use suitable extinguishing agents.
- Specific hazards : Pressurized container. On heating there is a risk of bursting due to internal pressure build-up.  
NOT flammable. However, it may present a risk in the event of a fire.  
Toxic vapours (halogen compounds) are released.  
Vapour / air mixture may be flammable under specific conditions.
- Specific fire fighting methods : Stay upwind.  
Evacuate the personnel away from the fumes.  
Cool down the containers/equipment exposed to heat with a water spray.
- Protection of fire-fighters : Self-contained breathing apparatus.
-

## SAFETY DATA SHEET

---

ISCEON 49

Page: 3/8

Date: 07/09/2004

Version: 3.03 UK

Cancels and replaces version: 2.00 UK

---

### 6 Accidental release measures

- Personal precautions : Avoid contact with skin and eyes.  
Do not breathe gas.  
NO naked flames.  
Do NOT smoke.  
For further information refer to section 8  
"Exposure-controls/personal protection".  
Heavy vapours. Shut off low-level openings in the vicinity  
(ventilation shafts, drains...).  
Prevent the product from entering cellars, basements or pits.  
Stop the leak.  
Ventilate spillage area.  
Ventilate basements.
- Environmental precautions : Prevent the product from spreading into the environment.  
Contain the spilled material by bunding.
- Methods for cleaning up
- Recovery : Recover as much of the product as possible.
  - Cleaning/Decontamination : Allow residual product to evaporate.
  - Disposal : For disposal of contaminated materials refer to section 13:  
"Disposal considerations".
- 

### 7 Handling and storage

#### HANDLING

- Technical measures : Ventilation.  
Use in a closed system.
- Measures : Avoid contact with hot surfaces.  
Avoid high temperatures.  
Smoking is forbidden.

#### STORAGE

- Technical measures : Storage facilities should be:  
equipped with ventilation at low level.  
Take all necessary precautions to avoid the accidental release of  
the product outside, due to the rupture of containers or transfer  
systems.
- Storage conditions
- Recommended : Keep:
    - the container tightly closed and dry.
    - in a cool, well-ventilated area.
    - at temperatures not exceeding 45°C.
    - away from any source of heat.
    - away from any source of ignition.
-

## SAFETY DATA SHEET

---

ISCEON 49

Page: 4/8

Date: 07/09/2004

Version: 3.03 UK

Cancels and replaces version: 2.00 UK

---

Incompatible products	:	Refer to the detailed list of incompatible materials (section 10 "Stability/Reactivity").
Packaging	:	Bulk product : consult the supplier. Pressurized metal container.
Packaging materials	:	
- Recommended	:	Steel.
- Not suitable	:	Magnesium and its alloys. Zinc and its alloys. Aluminium alloys containing more than 2% magnesium.

---

### 8 Exposure controls / personal protection

Engineering measures	:	Ensure good ventilation of the work station.
Control parameters	:	
Occupational exposure limits	:	
- Limits (UK)	:	1,1,1,2-Tetrafluoroethane (HFC 134a): OES: 1000 ppm (4240 mg/m <sup>3</sup> ). (Long term exposure limit - 8h TWA reference period).
Personal protective equipment	:	
- Respiratory protection	:	In the event of insufficient ventilation: Self-contained breathing apparatus.
- Hand protection	:	Handling refrigerated product: Protective gloves insulated against the cold.
- Eye protection	:	Handling refrigerated product: Goggles.
- Skin and body protection	:	Handling refrigerated product: Impermeable clothing.
Hygiene measures	:	Do NOT drink, eat or smoke in the workplace.

---

### 9 Physical and chemical properties

#### APPEARANCE

- Physical state	:	Compressed liquefied gas.
- Colour	:	colourless.
Odour	:	slightly ethereal.
pH	:	Not applicable
Specific temperatures	:	
- Boiling	:	-35°C.
Flammability characteristics	:	
- Flash point	:	Not applicable.
Oxidizing properties	:	Non oxidizing material according to EC criteria.

---

## SAFETY DATA SHEET

ISCEON 49

Page: 5/8

Date: 07/09/2004

Version: 3.03 UK

Cancels and replaces version: 2.00 UK

---

Vapour pressure : 683 kPa, at 20°C.  
Specific gravity : 1214 kg/m<sup>3</sup>, at 20°C.  
Solubility  
- in water : Slightly soluble.  
- in organic solvents : Soluble in:  
- common solvents.

---

### 10 Stability and reactivity

Stability : Stable at ambient temperature and under normal conditions of use.

Hazardous reactions

- Conditions to avoid : May decompose:  
- on contact with hot surfaces and flames.

- Materials to avoid : Reacts violently with:  
- alkali metals.  
- alkaline earth metals.  
- magnesium.  
- powdered metals.

- Hazardous decomposition products : On combustion or on thermal decomposition (pyrolysis) releases:  
toxic gases.  
(Fluorinated compounds).  
(Hydrofluoric acid).

---

### 11 Toxicological information

Acute toxicity : A : 1,1,1,2-Tetrafluoroethane:  
LC50 inhalation 4 h (Rat) : > 50 % [\*]  
(Unpublished reports)  
B : Octafluoropropane:  
LC 50 inhalation, 1h : > 800000 ppm. (Rat) [\*]  
C : IsoButane  
LC 50 inhalation, 2h : 520000 ppm. (Rat) [\*]  
(Published data).

Acute symptoms : Effects following high level exposure:  
Headaches.  
Dizziness.  
Loss of consciousness.  
Possible effects, following high level exposure:  
Cardiac disorders.  
Possibility of cardiac arrest.

Local effects : Contact with liquefied gas causes frostbite.  
A : Slightly irritating to rabbits on cutaneous application. [\*]

---

## SAFETY DATA SHEET

ISCEON 49

Page: 6/8

Date: 07/09/2004

Version: 3.03 UK

Cancels and replaces version: 2.00 UK

---

	A :Not irritating to rabbits on ocular application. (vapours) [*] (Published data). Contact with liquefied gas causes injury to the cornea.
Sensitisation	: not sensitising (maximisation test) (Guinea-pig) [*] (Unpublished internal reports)
Repeated dose toxicity	: A : Repeated dose toxicity (90 days) (Rat) by inhalation No observed effect level (NOEL) : 50000 ppm [*] (Unpublished reports) B : Repeated dose toxicity (10 days) (Rat) (Guinea-pig) by inhalation No observed effect level (NOEL) : 113000 ppm [*] (Published data).
Specific effects - Mutagenicity	: According to the data on the components Ames test. (with or without metabolic activation).Negative. [*] In vivo micronucleus test.(Mouse) Negative. [*] A : SCE test bacteria mutation test ( <i>E. coli</i> ) Point mutations : (with or without metabolic activation). UDS test (Rat)Chromosomal aberrations : (Rat) Negative. [*] (Published data).

---

### 12 Ecological information

#### MOBILITY

Volatility	: Product is volatile when in aqueous solution.
Expected behaviour of the product	: Ultimate destination of the product : AIR.

#### BIODEGRADABILITY

- Ultimate aerobic biodegradability	: No information available.
-------------------------------------	-----------------------------

#### BIOACCUMULATION

Octanol/water partition coefficient	: Not applicable
-------------------------------------	------------------

#### ECOTOXICITY

Effects on the aquatic environment	: No information available.
------------------------------------	-----------------------------

---

### 13 Disposal considerations

#### RESIDUES FROM PRODUCT

Prohibition	: Do not allow the product to be released into the environment.
Destruction/Disposal	: Consult the manufacturer or supplier for information regarding recovery and recycling of the product. If recovery is not possible: Incinerate at a licensed installation.

#### CONTAMINATED PACKAGING

---

## SAFETY DATA SHEET

ISCEON 49

Page: 7/8

Date: 07/09/2004

Version: 3.03 UK

Cancel and replaces version: 2.00 UK

---

Decontamination/cleaning	:	De-gas.
Destruction/Disposal	:	Re-usable containers: Return to the supplier. Disposable containers: Dispose of at an authorised land-fill site.
NOTE	:	The user's attention is drawn to the possible existence of local regulations regarding disposal.

---

### 14 Transport information

#### INTERNATIONAL REGULATIONS

##### Land

- Rail/road (RID/ADR) : UN number: 3163.  
Class:2.2.  
Hazard identification number: 20.  
Labelling: 2.2.

Sea (IMO/IMDG) : Class: 2.2.  
UN Number: 3163.  
Labelling: 2 NON FLAMMABLE GAS.  
Marine pollutant: NO.Emergency schedule (EmS): F-C, S-V.

Air (ICAO-IATA) : Class: 2.2.  
UN number: 3163.  
Labelling: 2 NON-FLAMMABLE GAS.  
Cargo aircraft : Packing instruction: 200 Quantity : 150 kg.  
Passenger aircraft: Packing instruction: 200 Quantity : 75 kg.

#### OTHER REGULATIONS

- United Kingdom: Rail/road : Substance identification number: 3163.  
Classification for conveyance: 2.2.  
Emergency action code: 2TE.

NOTE : The above regulatory prescriptions are those valid on the date of publication of this sheet.  
Given the possible evolution of transport regulations for hazardous materials, it would be advisable to check their validity with your sales office.

---

### 15 Regulatory information

#### LABELLING

EC regulations : Mandatory labelling (self-classification) of hazardous preparations: **NOT APPLICABLE**

- R phrases : No R phrases.

- S phrases : S 24/25: Avoid contact with skin and eyes.  
S 41: In case of fire and/or explosion do not breathe fumes.

---

## SAFETY DATA SHEET

---

ISCEON 49

Page: 8/8

Date: 07/09/2004

Version: 3.03 UK

Cancels and replaces version: 2.00 UK

---

### >>Further regulations

United Kingdom

: Handle in accordance with relevant British legislation:  
Control of Substances Hazardous to Health Regulations  
Environmental Hygiene Guidance: EH/40 Occupational  
Exposure Limits (revised annually).  
Environmental Protection Act  
Carriage of Dangerous Goods by Road Regulations  
Carriage of Dangerous Goods by Rail Regulations  
Carriage of Dangerous Goods by Road and Rail (Classification,  
Packaging and Labelling) and use of Transport Pressure  
Receptacles Regulations

NOTE

: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

---

## 16 Other information

R Phrases of § 2 & 3

: R 12: Extremely flammable. [**\***]

\* Update

: This sheet was updated (refer to the date at the top of this page). Subheadings and text which have been modified since the previous version are indicated with an asterisk (\*).

- European inventory (EINECS, ELINCS)

: All the constituents of this preparation are registered in the EINECS inventory.

- American inventory (TSCA)

: All the components of this preparation are registered in the TSCA inventory.

---

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfil his obligations regarding the use of hazardous products. This information is not exhaustive. This does not exonerate the user from ensuring that legal obligations, other than those mentioned, relating to the use and storage of the product, do not exist. This is solely his responsibility.