

# SAFETY DATA SHEET

DRAINCLEEN

Page 1

Issued: 08/01/2004

Revision No: 1

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** DRAINCLEEN  
**Company name:** Advanced Engineering Limited  
Guardian House  
Stroudley Road  
Basingstoke  
Hampshire  
RG24 8NL  
United Kingdom  
Tel: +44(0) 1256 46 03 00  
Fax: +44(0) 1256 46 22 66  
Emergency tel: +44(0) 1256 46 03 00

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** SULPHURIC ACID 30-50%  
EINECS: 231-639-5 CAS: 7664-93-9  
[C] R35

## 3. HAZARDS IDENTIFICATION

**Main hazards:** Causes severe burns.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** Irritation or pain may occur at the site of contact. Blistering may occur. Severe burns may occur.  
**Eye contact:** There may be irritation and redness. The eyes may water profusely. Corneal burns may occur.  
**Ingestion:** There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Corrosive burns may appear around the lips. Nausea and stomach pain may occur. There may be vomiting.  
**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath. There may be loss of consciousness.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.  
**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.  
**Ingestion:** Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.  
**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies

[cont...]

**SAFETY DATA SHEET**

DRAINCLEEN

down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available.  
Transfer to hospital as soon as possible.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Carbon dioxide. Alcohol or polymer foam. Dry chemical powder.

**Exposure hazards:** Corrosive. In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Refer to section 13 of SDS for suitable method of disposal. Wash the spillage site with large amounts of water.

**7. HANDLING AND STORAGE**

**Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Occupational exposure limits**

**TWA (8 hr exposure limit):** 0.3 mg/m<sup>3</sup> (OES)

**Hazardous ingredients:** SULPHURIC ACID...100%

TWA (8 hr exposure limit): 1 mg/m<sup>3</sup> (OES)

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety goggles. Face-shield. Ensure eye bath is to hand.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck. Boots made of PVC. PVC apron covering the tops of the boots. Ensure safety shower is to hand.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** Brown

**Odour:** Characteristic odour

**Viscosity:** Viscous

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat.

**Materials to avoid:** Strong bases. Oxidising agents. Reducing agents. Organic materials.

**Haz. decomp. products:** In combustion emits toxic fumes of sulphur oxides.

**SAFETY DATA SHEET**

DRAINCLEEN

**11. TOXICOLOGICAL INFORMATION**

**Hazardous ingredients:** SULPHURIC ACID...100%  
ORL RAT LD50 2140 mg/kg

**Chronic toxicity:** Danger of serious damage to health by prolonged exposure through inhalation. Danger of serious damage to health by prolonged exposure in contact with skin.

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Soluble in water.

**Persistence and degradability:** Biodegradable in part only.

**Bioaccumulative potential:** Slightly bioaccumulable.

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms. Toxic to flora. Toxic to fauna. Adverse effects on water treatment plants.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** D10 Incineration on land.

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

<b>UN no:</b> 1760	<b>ADR Class:</b> 8
<b>Packing group:</b> II	<b>Classification code:</b> C9
<b>Shipping name:</b> CORROSIVE LIQUID, N.O.S.	
<b>Labelling:</b> 8	<b>Hazard ID no:</b> 80

**IMDG / IMO**

<b>UN no:</b> 1760	<b>Class:</b> 8
<b>Packing group:</b> II	<b>EmS:</b> F-A,S-B
<b>Marine pollutant:</b> .	<b>Labelling:</b> 8

**IATA / ICAO**

<b>UN no:</b> 1760	<b>Class:</b> 8
<b>Packing group:</b> II	<b>Packing instructions:</b> 808(P&CA); 812(CAO)
<b>Labelling:</b> 8	

## SAFETY DATA SHEET

DRAINKLEEN

### 15. REGULATORY INFORMATION

**Hazard symbols:** Corrosive.



**Risk phrases:** R35: Causes severe burns.

**Safety phrases:** S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

### 16. OTHER INFORMATION

**Risk phrases used in s.2:** R35: Causes severe burns.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.