

COMPRESSOR DEFINITION

Designation	EM T6152GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	912FA67

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	4.50	[cm ³] (0.275 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	13.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.8	[kg] (17.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-34	
3 Start capacitor	43-53(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0827/G6	
6 Start winding resistance	[Ω at 25°C (77°F)] +/- 8%	
7 Run winding resistance	[Ω at 25°C (77°F)] +/- 8%	
8 LRA - Locked rotor amperage (50 Hz)	8.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2586	652	758	329	1.77	21.29	7.86	1.98	2.30

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1254	316	367	179	1.22	7.95	7.00	1.76	2.05
-15	(+ 5)	1548	390	454	194	1.26	9.89	7.98	2.01	2.34
-10	(+14)	1891	477	554	208	1.31	12.15	9.09	2.29	2.66
-5	(+23)	2287	576	670	222	1.36	14.80	10.32	2.60	3.02
0	(+32)	2740	691	803	235	1.41	17.88	11.65	2.94	3.41
+5	(+41)	3255	820	954	249	1.46	21.47	13.09	3.30	3.84
+10	(+50)	3836	967	1124	262	1.51	25.61	14.63	3.69	4.29

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1061	267	311	192	1.26	7.43	5.54	1.40	1.62
-15	(+ 5)	1323	333	388	211	1.32	9.33	6.27	1.58	1.84
-10	(+14)	1626	410	477	229	1.38	11.54	7.09	1.79	2.08
-5	(+23)	1976	498	579	247	1.45	14.13	7.99	2.01	2.34
0	(+32)	2376	599	696	264	1.52	17.16	8.98	2.26	2.63
+5	(+41)	2830	713	829	282	1.59	20.68	10.03	2.53	2.94
+10	(+50)	3343	842	980	300	1.66	24.75	11.16	2.81	3.27

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	872	220	255	202	1.29	6.86	4.32	1.09	1.26
-15	(+ 5)	1094	276	321	226	1.37	8.66	4.83	1.22	1.42
-10	(+14)	1351	340	396	250	1.46	10.77	5.40	1.36	1.58
-5	(+23)	1647	415	483	274	1.55	13.26	6.03	1.52	1.77
0	(+32)	1986	501	582	297	1.64	16.18	6.70	1.69	1.96
+5	(+41)	2373	598	695	320	1.73	19.58	7.41	1.87	2.17
+10	(+50)	2812	709	824	344	1.82	23.53	8.17	2.06	2.39

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.86 +0.07/+0.00	[mm]	(0.191" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		