IEU KO CELLAR STAR







Cellar cooling system

The new KD Cellar Star is a high performance cooling system designed to control cellar temperature to maintain beer and wine in optimum condition.

Product features:

- Housed outdoor unit equipped with a rotary compressor
- Includes microchannel condenser, liquid receiver, refrigerant charge and service valves
- Acoustically lined compressor compartment for noise reduction
- Dixell electronic controller with off cycle defrost
- LP Safety switch
- R410A Sporlan expansion valve and contactor
- Long lasting white powder coated finish
- Indoor unit comes with hinged side panels for easy access

ORDER NOW

0121 666 4700 sales@thermofrostcryo.co.uk



KD CELLAR STAR

Performance data - R410A

Indoor / Outdoor		Cooling capacity (watts) Ambient 32°C Room Temperature °C						Above Ground	Below Ground
	4°C 6°C 8°C 10°C 12.7°C 14°C 16°C					m³			
SC040/PAP015M1	2,906	3,099	3,325	3,462	3,836	3,931	4,084	45	55
SC045/PAP020M1	3,819	4,083	4,344	4,503	4,940	5,056	5,242	57	90
SC050/PAP025M1	4,390	4,737	5,074	5,203	5,749	5,975	6,116	70	120
SC070/PAP028M1	5,888	6,247	6,754	6,911	7,592	7,875	8,047	120	155

Technical data

Model	Nominal	Airflow	Airflow	Pipe	Pipework		Max pipe run	
	Kw	m3/hr indoor	m3/hr outdoor	Liquid	Suction	Length	Rise	
SC040/PAP015M1	3,836	3,439	1,800	1/4"	1/2"	25	5	
SC045/PAP020M1	4,940	3,310	2,400	1/4"	1/2"	25	8	
SC050/PAP025M1	5,749	3,310	2,520	1/4"	5/8"	25	8	
SC070/PAP028M1	7,592	3,648	2,460	3/8"	5/8"	25	8	

Model	Power Supply	FLA Amps	LRA Amps	Interconnecting cable	Fuse Rating
SC040/PAP015M1	230/1/50	6.8	24	3 Core	16
SC045/PAP020M1	230/1/50	8.2	36	3 Core	20
SC050/PAP025M1	230/1/50	9.7	39	3 Core	25
SC070/PAP028M1	230/1/50	10.9	62	3 Core	25

System charge

Outdoor Model	Pre-charge Kg	Max pipe run (m)	Additional charge g/m
PAP015M1	1.0	25	N/A
PAP020M1	1.0	13	22
PAP025M1	1.5	25	N/A
PAP028M1	1.5	8	52

The maximum pipe run must include the rise, it is not additional to the length. Air throw of SC cooler is 11m with 0.25 m/s terminal air velocity.

Physical

Model	Width (mm)	Depth (mm)	Height (mm)	Weight (Kg)
SC040	840	327	590	26
SC045	840	327	590	28
SC050	840	327	590	28
SC070	1040	327	590	41
PAP015M1	702	342	612	48
PAP020M1	860	342	706	55
PAP025M1	860	342	810	59
PAP028M1	860	342	810	67

