

AMBIENT TEMPERATURE		TEMP. COEFF.	KTY81-121			
(°C)	(°F)	(%/°K)	RESISTANCE (Ω)			TEMP. ERROR (K)
			MIN.	TYP.	MAX.	
-55	-67	0.99	471	485	500	±3.02
-50	-58	0.98	495	510	524	±2.92
-40	-40	0.96	547	562	576	±2.74
-30	-22	0.93	603	617	632	±2.55
-20	-4	0.91	662	677	691	±2.35
-10	14	0.88	726	740	754	±2.14
0	32	0.85	794	807	820	±1.91
10	50	0.83	865	877	889	±1.67
20	68	0.80	941	951	962	±1.41
25	77	0.79	980	990	1000	±1.27
30	86	0.78	1018	1029	1041	±1.39
40	104	0.75	1097	1111	1125	±1.64
50	122	0.73	1180	1196	1213	±1.91
60	140	0.71	1266	1286	1305	±2.19
70	158	0.69	1355	1378	1402	±2.49
80	176	0.67	1447	1475	1502	±2.8
90	194	0.65	1543	1575	1607	±3.12
100	212	0.63	1642	1679	1716	±3.46
110	230	0.61	1745	1786	1828	±3.83
120	248	0.58	1849	1896	1943	±4.33
125	257	0.55	1900	1950	2000	±4.66
130	266	0.52	1950	2003	2056	±5.07
140	284	0.45	2044	2103	2162	±6.28
150	302	0.35	2124	2189	2254	±8.55