



INDICATIVE PRODUCT IMAGE

Product file

Type	Compact
Mounting	Wall
Code	BYWT352LA60P11
Range	BYWT
Version	Plug-in
Noise	35.3 dBA 10 m
Condensation	Air
Net weight	107 kg
PED	0
Defrost	Hot gas
Expansion	Valve
Application	LBP
Refrigerant	R290

Dimensions

Width L	711 mm
Depth P	1254 mm
Height H	828 mm

Absorptions

Power consumption	1800 W
Current consumption	9.8 A

Condenser

Diameter	350 mm
Air flow	2540 m³/h


Unit cooler

Fan-motors no.	1
Diameter	350 mm
Air flow	2740 m³/h
Air throw	8 m


Compressor

Type	Hermetic
Compressors no.	2
Brand	EMBRACO
Voltage	230/1/50
Displacement	2 X 27.8 cm³

Technical data - BYWT352LA60P11



Technical data - BYWT352LA60P11



Refrigerating capacity table (W) - BYWT352LA60P11 - Refrigerant: R290

TA \ Tcella	-25 °C	-20 °C	-15 °C	-10 °C	-5 °C
25 °C	1939 (25.7 m³)	2313 (40.8 m³)	2720 (64.9 m³)	3157 (106 m³)	3623 (181 m³)
32 °C	1812 (18.6 m³)	2165 (29.6 m³)	2549 (46.8 m³)	2962 (74.8 m³)	3400 (123 m³)
38 °C	1688 (12.1 m³)	2023 (21.7 m³)	2388 (34.2 m³)	2779 (54.2 m³)	3195 (88.2 m³)
43 °C	1579 (9.3 m³)	1899 (15.8 m³)	2248 (25.8 m³)	2621 (40.6 m³)	3017 (64.9 m³)

Values referred to :

Suction gas : +20°C

Subcooling : 0K

Superheat : 100%

Tamb : +32°C

Compressor absorption :

Te -5°C (HBP); Tcond +50°C
Te -10°C (MBP); Tcond +50°C
Te -30°C (LBP); Tcond +50°C



INDICATIVE PRODUCT IMAGE

MECHANICAL PART MAIN COMPONENTS

- Hermetic compressors with thermal motor protection
- Condenser with Ø5mm tubes with internal spiral rifling
- Evaporator with Ø5/16" tubes with internal spiral rifling
- Electronic fan-motors on both condenser and evaporator
- Mechanical thermostatic valve supplied standard across the entire range
- Hot gas defrosting
- Evaporating water tray
- R290 refrigerant charge ≤ 150g per circuit

CONTROL CIRCUIT and ELECTRICAL PART

- Safety pressure switch on high pressure side
- Door micro-switch wired with cable L= 2.5
- Door heater cable on LT models (L = 2.5m)
- LED cold room light with cable L= 5m
- Power supply cable L= 2.5 m with wired electrical plug
- Industrial Plug (2P+E or 3P+N+E) 16 A
- Industrial Plug (2P+E) 32 A only on BEWx352MA80P11 and BEWx352LA60P11

ELECTRONIC CONTROL

- Electronic board that can be programmed according to different user requirements
- Connection cable for BMS (RTU Modbus Protocol) L=5 m
- integral control panel

STRUCTURE

- Self-supporting frame in galvanized metal sheet
- Easily removable housing for a rapid access to the components in case of inspection or maintenance
- Installation kit complete with screws and washers to secure the packaged system to the wall of the coldroom and sealing putty in strips for insulation
- Plug-in thickness 100 mm for MT models and 150 mm for BT models (WT models)

OPTIONAL ITEMS

- Plug-in insulation kits supplied separately for saddle models (WS): 100mm, 150mm, 200mm
- Extension cable kits L=5m and L=10m (coldroom light cable, door heater cable, micro-switch cable)
- Presetting for Master & Slave (cable L=5m)