



INDICATIVE PRODUCT IMAGE

Product file

Code	SFL006P001
Gas	R290
Application	LBP
Series	SF
Expansion	Capillary
Exchange	Air
Net weight	52 kg
Ped	0
Defrost	Hot gas
Mounting	Ceiling
Type	Compact

Compressor

Compressor no.	1
Compressor type	Hermetic
Compressor brand	EMBRACO
Compressor voltage	220-240/1/50

Condenser

Fan-motors no.	1
Fan blade diameter	300 mm
Condenser air flow	886 m³/h

Evaporator

Fan-motors no.	1
Fan blade diameter	200 mm
Evaporator speed	Low speed
Air throw	3.00 m
Evaporator air flow	578 m³/h

Absorptions

Power absorbed	588 W
Current absorbed	3.37 A
Maximum current	7.00 A

Dimensions

Width	700 mm
Depth	880 mm
Height	520 mm

Refrigeration capacity table – SFL006P001 – Refrigerant: R290

Ambient temperature	Cell temperature	Cell volume	Capacity
25 °C	-25 °C	4.00 m³	763 W
25 °C	-20 °C	5.90 m³	916 W
25 °C	-15 °C	7.80 m³	1083 W
32 °C	-25 °C	3.70 m³	723 W
32 °C	-20 °C	5.40 m³	873 W
32 °C	-15 °C	7.00 m³	1037 W
43 °C	-25 °C	3.00 m³	660 W
43 °C	-20 °C	4.60 m³	805 W
43 °C	-15 °C	5.90 m³	963 W

Values referred to :

Suction gas : +0°C (LT) e +20°C (HT)

Subcooling : 0K


Superheat : 100%

Compressor absorption :

Te -10°C (HT/MT); Tcond +50°C

Te -30°C (LT); Tcond +50°C

Technical drawings – SFL006P001





INDICATIVE PRODUCT IMAGE

• GENERAL FEATURES

- Self-supporting casing in zinc-plated metal sheet, which is coated with epoxy powder and easily removable panels for fast access to components during inspection or maintenance operations
- Hermetic compressors with thermal motor protection
- Heat exchangers with copper and aluminium blocks
- Condenser with Ø5mm tubes with internal spiral rifling
- Condensation by air (optional by water)
- Automatic defrosting with programmable run, duration and frequency settings
- Electronic board that can be programmed according to different user requirements
- Control panel installed in a remote position
- Electronic control panel
- High pressure switch
- Remote control panel (5m)
- Door micro switch with 2,5m long cable
- Evaporating water tray
- Door heater cable for LBP items with 2,5m long cable
- Power supply cable (L=2,5m)
- Mounting set and overflow tube
- Package included