



INDICATIVE PRODUCT IMAGE

Product file

Code	SFM006P001
Gas	R290
Application	MBP
Series	SF
Expansion	Capillary
Exchange	Air
Net weight	53 kg
Ped	0
Defrost	Hot gas
Mounting	Ceiling
Type	Compact

Compressor

Compressor no.	1
Compressor type	Hermetic
Compressor brand	EMBRACO
Compressor voltage	220-240/1/50

Condenser

Fan-motors no.	1
Fan blade diameter	300 mm
Condenser air flow	886 m³/h

Evaporator

Fan-motors no.	1
Fan blade diameter	200 mm
Evaporator speed	Low speed
Air throw	3.00 m
Evaporator air flow	578 m³/h

Absorptions

Power absorbed	582 W
Current absorbed	4.19 A
Maximum current	7.00 A

Dimensions

Width	700 mm
Depth	880 mm
Height	520 mm

Refrigeration capacity table – SFM006P001 – Refrigerant: R290

Ambient temperature	Cell temperature	Cell volume	Capacity
25 °C	-5 °C	6.30 m³	987 W
25 °C	0 °C	7.80 m³	1135 W
25 °C	5 °C	12.20 m³	1291 W
32 °C	-5 °C	5.80 m³	929 W
32 °C	0 °C	7.20 m³	1069 W
32 °C	5 °C	11.80 m³	1217 W
43 °C	-5 °C	5.30 m³	835 W
43 °C	0 °C	5.60 m³	962 W
43 °C	5 °C	9.00 m³	1097 W

Values referred to :

Suction gas : +0°C (LT) e +20°C (HT)

Subcooling : 0K


Superheat : 100%

Compressor absorption :

Te -10°C (HT/MT); Tcond +50°C

Te -30°C (LT); Tcond +50°C

Technical drawings – SFM006P001





INDICATIVE PRODUCT IMAGE

• GENERAL FEATURES

- Self-supporting casing in zinc-plated metal sheet, which is coated with epoxy powder and easily removable panels for fast access to components during inspection or maintenance operations
- Hermetic compressors with thermal motor protection
- Heat exchangers with copper and aluminium blocks
- Condenser with Ø5mm tubes with internal spiral rifling
- Condensation by air (optional by water)
- Automatic defrosting with programmable run, duration and frequency settings
- Electronic board that can be programmed according to different user requirements
- Control panel installed in a remote position
- Electronic control panel
- High pressure switch
- Remote control panel (5m)
- Door micro switch with 2,5m long cable
- Evaporating water tray
- Door heater cable for LBP items with 2,5m long cable
- Power supply cable (L=2,5m)
- Mounting set and overflow tube
- Package included